

## 100 μL, Model 1710 FN CTC SYR (6.6 mm), C-Line, Fixed NDL, 26s ga, point style AS

Specification Sheet (Part/REF # 203076)



Hamilton offers a wide range of quality syringe options for the PAL GC and Combi PAL (Headspace) GC Autosamplers.

## **Product Specifications**

Volume	100 μL
Syringe Type	Gastight
Syringe Series	1700
Termination	Fixed Needle (FN)
Needle	Fixed Needle, no glue or cement
Gauge	26s gauge
Point Style	AS
Needle Length	2.00 in (50.8 mm)
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	20°C / 68°F
Needle Inner Diameter	0.005 inches (0.13 mm)
Needle Outer Diameter	0.019 inches (0.483 mm)
Std Needle Dead Volume	0.64 μL



Visit <u>www.hamiltoncompany.com/support</u> to find a representative in your area or call us:

US: +1-800-648-5950 EU: +40-356-635-055



Sales Quantity 1 syringe per pack

Specifications are subject to change without notice

Spec. Version B

https://www.hamiltoncompany.com/laboratory-products/syringes/203076



Visit <a href="https://www.hamiltoncompany.com/support">www.hamiltoncompany.com/support</a> to find a representative in your area or call us:

US: +1-800-648-5950 EU: +40-356-635-055