

## 500 μL, Model 1750 FN CTC SYR (7.9 mm), C-Line, Fixed NDL, 26 ga, point style AS

Specification Sheet (Part/REF # 203080)



Hamilton offers a wide range of quality syringe options for the PAL GC and Combi PAL (Headspace) GC Autosamplers.

## **Product Specifications**

Volume	500 μL
Syringe Type	Gastight
Syringe Series	1700
Termination	Fixed Needle (FN)
Needle	Fixed Needle, no glue or cement
Gauge	26 gauge
Point Style	AS
Needle Length	2.00 in (50.8 mm)
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	700 psig (48.3 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	20°C / 68°F
Needle Inner Diameter	0.005 inches (0.13 mm)
Needle Outer Diameter	0.0187 inches (0.47 mm)
Std Needle Dead Volume	2.70 μL



Visit  $\underline{www.hamiltoncompany.com/support}$  to find a representative in your area or call us:

US: +1-800-648-5950 EU: +40-356-635-055



Sales Quantity 1 syringe per pack

Specifications are subject to change without notice

Spec. Version B

https://www.hamiltoncompany.com/laboratory-products/syringes/203080



Visit <a href="https://www.hamiltoncompany.com/support">www.hamiltoncompany.com/support</a> to find a representative in your area or call us:

US: +1-800-648-5950 EU: +40-356-635-055