

# 10 $\mu$ L, Model 1701 N CTC SYR (6.6 mm), Cemented NDL, 22s ga, 51 mm, point style 3

Specification Sheet (Part/REF # 203560)

## Product Specifications

<b>Volume</b>	10 $\mu$ L
<b>Syringe Type</b>	Gastight
<b>Syringe Series</b>	1700
<b>Termination</b>	Cemented Needle (N)
<b>Needle</b>	Cemented Needle
<b>Gauge</b>	22s gauge
<b>Point Style</b>	3
<b>Needle Length</b>	2 inch (51 mm)
<b>Fluid Path</b>	SST, borosilicate glass, PTFE
<b>Autoclavable</b>	No
<b>Gas Sterilizable</b>	Yes
<b>Pressure</b>	1000 psig (68.9 bar)
<b>Maximum Temperature</b>	50°C / 122°F
<b>Minimum Temperature</b>	20°C / 68°F
<b>Needle Inner Diameter</b>	0.005 inches (0.13 mm)
<b>Needle Outer Diameter</b>	0.028 inches (0.711 mm)
<b>Std Needle Dead Volume</b>	1.13 $\mu$ L
<b>Sales Quantity</b>	1 syringe per pack

Specifications are subject to change without notice

<https://www.hamiltoncompany.com/laboratory-products/syringes/203560>

**Spec. Version B**

