

## 5 μL, Model 75 N SYR, Cemented NDL, 26s ga, 50 mm, point style AS

Specification Sheet (Part/REF # 204051)



## **Product Specifications**

Volume	5 μL
Syringe Type	Microliter
Syringe Series	700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	26s gauge
Point Style	AS
Needle Length	1.97 in (50.0 mm)
Fluid Path	SST, borosilicate glass
Autoclavable	
Autociavable	No
Gas Sterilizable	Yes
Gas Sterilizable	Yes
Gas Sterilizable Pressure	Yes 2000 psig (137.9 bar)
Gas Sterilizable Pressure Maximum Temperature	Yes 2000 psig (137.9 bar) 50°C / 122°F
Gas Sterilizable  Pressure  Maximum Temperature  Minimum Temperature	Yes  2000 psig (137.9 bar)  50°C / 122°F  20°C / 68°F
Gas Sterilizable  Pressure  Maximum Temperature  Minimum Temperature  Needle Inner Diameter	Yes  2000 psig (137.9 bar)  50°C / 122°F  20°C / 68°F  0.005 inches (0.13 mm)



EU: +40-356-635-055



Specifications are subject to change without notice <a href="https://www.hamiltoncompany.com/laboratory-products/syringes/204051">https://www.hamiltoncompany.com/laboratory-products/syringes/204051</a>

Spec. Version B



Visit <a href="https://www.hamiltoncompany.com/support">www.hamiltoncompany.com/support</a> to find a representative in your area or call us:

US: +1-800-648-5950 EU: +40-356-635-055