

10 μL, Model 701 N CTC SYR(6.6 mm), S-Line, CementedNeedle, 26s ga, point style AS

Specification Sheet (Part/REF # 67438-01)



Hamilton offers a wide range of quality syringe options for the PAL GC and Combi PAL (Headspace) GC Autosamplers.

Product Specifications

Volume	10 μL
Syringe Type	Microliter
Syringe Series	700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	26s gauge
Point Style	AS
Needle Length	2.00 in (50.8 mm)
Fluid Path	SST, borosilicate glass
Autoclavable	No
Gas Sterilizable	Yes
Pressure	2000 psig (137.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	20°C / 68°F
Needle Inner Diameter	0.0045 inches (0.11 mm)
Needle Outer Diameter	0.0187 inches (0.47 mm)
Std Needle Dead Volume	0.64 μL



Visit $\underline{www.hamiltoncompany.com/support}$ to find a representative in your area or call us:

US: +1-800-648-5950 EU: +40-356-635-055



Sales Quantity 1 syringe per pack

Specifications are subject to change without notice

Spec. Version B

https://www.hamiltoncompany.com/laboratory-products/syringes/67438-01



Visit www.hamiltoncompany.com/support to find a representative in your area or call us:

US: +1-800-648-5950 EU: +40-356-635-055