

## 500 μL, Model 1750 RN SYR, Needle Sold Separately

Specification Sheet (Part/REF # 7658-01)



The 1700 series syringes are the gas tight version of the original 700 series syringes. This series of gas tight syringes is ideal for dispensing volumes from 1  $\mu$ L up to 500  $\mu$ L. A variety of different terminations and needle options are available in this series.

## **Product Specifications**

Volume	500 μL
Syringe Type	Gastight
Syringe Series	1700
Termination	Removable Needle (RN)
Needle	Large RN
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	Yes
Gas Sterilizable	Yes
Pressure	700 psig (48.3 bar)
Maximum Temperature	115°C / 239°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.128 inches (3.26 mm)



US: +1-800-648-5950 EU: +40-356-635-055



Std Needle Dead Volume N/A   Sales Quantity 1 syringe per pack	cifications are subject to change without no	Spec. Version
Std Needle Dead Volume N/A	s Quantity	
	Needle Dead Volume	
Barrel Outer Diameter 0.305 inches (7.75 mm)	el Outer Diameter	

US: +1-800-648-5950 EU: +40-356-635-055