

# 10 µL, Model 1701 RN SYR, Small Removable NDL, 32 ga, 2 in, point style 3

Specification Sheet (Part/REF # 80014)



The 1700 series syringes are the gas tight version of the original 700 series syringes. This series of gas tight syringes is ideal for dispensing volumes from 1 µL up to 500 µL. A variety of different terminations and needle options are available in this series.

## Product Specifications

<b>Volume</b>	10 µL
<b>Syringe Type</b>	Gastight
<b>Syringe Series</b>	1700
<b>Termination</b>	Removable Needle (RN)
<b>Needle</b>	Small RN
<b>Gauge</b>	32 gauge
<b>Point Style</b>	3
<b>Needle Length</b>	2 inch (51 mm)
<b>Fluid Path</b>	SST, borosilicate glass, PTFE
<b>Autoclavable</b>	Yes
<b>Gas Sterilizable</b>	Yes
<b>Pressure</b>	1000 psig (68.9 bar)
<b>Maximum Temperature</b>	115°C / 239°F
<b>Minimum Temperature</b>	10°C / 50°F
<b>Barrel Inner Diameter</b>	0.018 inches (0.460 mm)

---

<b>Barrel Outer Diameter</b>	0.260 inches (6.60 mm)
<b>Needle Inner Diameter</b>	0.0045 inches (0.11 mm)
<b>Needle Outer Diameter</b>	0.00925 inches (0.24 mm)
<b>Std Needle Dead Volume</b>	0.47 $\mu$ L
<b>Sales Quantity</b>	1 syringe per pack

---

Specifications are subject to change without notice

**Spec. Version B**

<https://www.hamiltoncompany.com/laboratory-products/syringes/80014>