HAMILT®N

10 μL, Model 1701 N Agilent SYR, Cemented NDL, 23s ga, 1.71 in, point style AS

Specification Sheet (Part/REF # 80080)



Product Specifications

Volume	10 µL
Syringe Type	Gastight
Syringe Series	1700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	23s gauge
Point Style	AS
Needle Length	1.71 inch (43.4 mm)
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	50°C / 122°F
Maximum Temperature Minimum Temperature	50°C / 122°F 10°C / 50°F
Minimum Temperature	10°C / 50°F
Minimum Temperature Barrel Inner Diameter	10°C / 50°F 0.018 inches (0.460 mm)
Minimum Temperature Barrel Inner Diameter Barrel Outer Diameter	10°C / 50°F 0.018 inches (0.460 mm) 0.260 inches (6.60 mm)



Visit <u>www.hamiltoncompany.com/support</u> to find a representative in your area or call us: US: +1-800-648-5950 EU: +40-356-635-055

HAMILTON

Std Needle Dead Volume

0.46 μL

1 syringe per pack

Specifications are subject to change without notice

https://www.hamiltoncompany.com/laboratory-products/syringes/80080

Spec. Version B



Visit <u>www.hamiltoncompany.com/support</u> to find a representative in your area or call us: US: +1-800-648-5950 EU: +40-356-635-055