HAMILT®N

10 μL, Model 701 N SYR, Cemented NDL, 26s ga, 2.75 in, point style 2

Specification Sheet (Part/REF # 80350)

The 700 series syringe is the original hand-fitted Hamilton syringe. This series of syringes is ideal for dispensing volumes from 0.5 μ L up to 500 μ L. A variety of different terminations and needle options are available in this series.

Contraction of the second

Product Specifications

Volume	10 μL
Syringe Type	Microliter
Syringe Series	700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	26s gauge
Point Style	2
Needle Length	2.75 in (69.9 mm)
Fluid Path	SST, borosilicate glass
Autoclavable	No
Gas Sterilizable	Yes
Pressure	2000 psig (137.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.019 inches (0.485 mm)
Barrel Outer Diameter	0.260 inches (6.60 mm)

HAMILT@N

Visit <u>www.hamiltoncompany.com/support</u> to find a representative in your area or call us: US: +1-800-648-5950 EU: +40-356-635-055

HAMILT@N[®]

https://www.hamiltoncompany.com/laboratory-products/syringes/80350

HAMILT®N

Visit **www.hamiltoncompany.com/support** to find a representative in your area or call us: US: +1-800-648-5950 EU: +40-356-635-055