## HAMILT®N

## 25 μL, Model 702 N SYR, Cemented NDL, 22s ga, 2 in, point style 5

Specification Sheet (Part/REF # 80439)



The 700 series syringe is the original hand-fitted Hamilton syringe. This series of syringes is ideal for dispensing volumes from 0.5  $\mu$ L up to 500  $\mu$ L. A variety of different terminations and needle options are available in this series.

## **Product Specifications**

Volume	25 μL
Syringe Type	Microliter
Syringe Series	700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	22s gauge
Point Style	5
Needle Length	2 inch (51 mm)
Fluid Path	SST, borosilicate glass
Autoclavable	No
Gas Sterilizable	Yes
Pressure	2000 psig (137.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.029 inches (0.729 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)



Visit <u>www.hamiltoncompany.com/support</u> to find a representative in your area or call us: US: +1-800-648-5950 EU: +40-356-635-055

## HAMILT@N<sup>®</sup>

Specifications are subject to change without notice		Spec. Version B
Sales Quantity	1 syringe per pack	
Std Needle Dead Volume	1.13 μL	
Needle Outer Diameter	0.0283 inches (0.72 mm)	
Needle Inner Diameter	0.0059 inches (0.15 mm)	

https://www.hamiltoncompany.com/laboratory-products/syringes/80439



Visit **www.hamiltoncompany.com/support** to find a representative in your area or call us: US: +1-800-648-5950 EU: +40-356-635-055