

100 μL Microliter Syringe Model 710 N, Cemented Needle, 22s gauge, 2 in, point style 3

Specification Sheet (Part/REF # 80665)



The 700 series syringe is the original hand-fitted Hamilton syringe. This series of syringes is ideal for dispensing volumes from $0.5~\mu L$ up to $500~\mu L$. A variety of different terminations and needle options are available in this series.

Product Specifications

Volume	100 μL
Syringe Type	Microliter
Syringe Series	700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	22s gauge
Point Style	3
Needle Length	2 inch (51 mm)
Fluid Path	SST, borosilicate glass
Autoclavable	No
Gas Sterilizable	Yes
Pressure	2000 psig (137.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.061 inches (1.46 mm)



US: +1-800-648-5950 EU: +40-356-635-055



Specifications are subject to change without notice	S	pec. Version B
Sales Quantity	1 syringe per pack	
Std Needle Dead Volume	1.13 μL	
Needle Outer Diameter	0.0283 inches (0.72 mm)	
Needle Inner Diameter	0.0059 inches (0.15 mm)	
Barrel Outer Diameter	0.305 inches (7.75 mm)	

https://www.hamiltoncompany.com/laboratory-products/syringes/80665



US: +1-800-648-5950 EU: +40-356-635-055