

250 μL, Model 725 N SYR, Cemented NDL, 22 ga, 2 in, point style 5

Specification Sheet (Part/REF # 80739)



The 700 series syringe is the original hand-fitted Hamilton syringe. This series of syringes is ideal for dispensing volumes from $0.5~\mu L$ up to $500~\mu L$. A variety of different terminations and needle options are available in this series.

Product Specifications

Volume	250 μL
Syringe Type	Microliter
Syringe Series	700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	22s gauge
Point Style	5
Needle Length	2 inch (51 mm)
Fluid Path	SST, borosilicate glass
Autoclavable	No
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.091 inches (2.30 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)



US: +1-800-648-5950 EU: +40-356-635-055



Needle Inner Diameter	0.0161 inches (0.41 mm)	
Needle Outer Diameter	0.0283 inches (0.72 mm)	
Std Needle Dead Volume	1.13 μL	
Sales Quantity	1 syringe per pack	
Specifications are subject to change without notice		Spec. Version B

https://www.hamiltoncompany.com/laboratory-products/syringes/80739



US: +1-800-648-5950 EU: +40-356-635-055