

500 μL Microliter Syringe Model 750 N, Cemented Needle, 22 gauge, 2 in, point style 3

Specification Sheet (Part/REF # 80865)



The 700 series syringe is the original hand-fitted Hamilton syringe. This series of syringes is ideal for dispensing volumes from $0.5~\mu L$ up to $500~\mu L$. A variety of different terminations and needle options are available in this series.

Product Specifications

Volume	500 μL
Syringe Type	Microliter
Syringe Series	700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	22 gauge
Point Style	3
Needle Length	2 inch (51 mm)
Fluid Path	SST, borosilicate glass
Autoclavable	No
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.135 inches (3.26 mm)



US: +1-800-648-5950 EU: +40-356-635-055



Specifications are subject to change without notice	Sp	ec. Version B
Sales Quantity	1 syringe per pack	
Std Needle Dead Volume	6.81 μL	
Needle Outer Diameter	0.0283 inches (0.72 mm)	
Needle Inner Diameter	0.0161 inches (0.41 mm)	
Barrel Outer Diameter	0.305 inches (7.75 mm)	

https://www.hamiltoncompany.com/laboratory-products/syringes/80865



US: +1-800-648-5950 EU: +40-356-635-055