

**50 µL, Model 1705 N SYR,  
Cemented NDL, 22 ga, 2 in,  
point style 3T**

Specification Sheet (Part/REF # 80950)



The needles on Thin Layer Chromatography (TLC) syringes are coated from the point for 3/4" with a PTFE-coating. The coating reduces the surface tension between the needle and the liquid making it ideal for reproducible sample spotting.

## Product Specifications

<b>Volume</b>	50 µL
<b>Syringe Type</b>	Gastight
<b>Syringe Series</b>	1700
<b>Termination</b>	Cemented Needle (N)
<b>Needle</b>	Cemented Needle
<b>Gauge</b>	22 gauge
<b>Point Style</b>	3T
<b>Needle Length</b>	2 inch (51 mm)
<b>Fluid Path</b>	SST, borosilicate glass, PTFE
<b>Autoclavable</b>	No
<b>Gas Sterilizable</b>	Yes
<b>Pressure</b>	1000 psig (68.9 bar)
<b>Maximum Temperature</b>	50°C / 122°F
<b>Minimum Temperature</b>	10°C / 50°F
<b>Barrel Inner Diameter</b>	0.041 inches (1.03 mm)
<b>Barrel Outer Diameter</b>	0.305 inches (7.75 mm)

---

<b>Needle Inner Diameter</b>	0.0161 inches (0.41 mm)
<b>Needle Outer Diameter</b>	0.0283 inches (0.72 mm)
<b>Std Needle Dead Volume</b>	6.81 $\mu$ L
<b>Sales Quantity</b>	1 syringe per pack

---

Specifications are subject to change without notice

**Spec. Version B**

<https://www.hamiltoncompany.com/laboratory-products/syringes/80950>