

100 μL, Model 1710 Luer Tip (LT) Threaded Plunger Syringe, Needle Sold Separately

Specification Sheet (Part/REF # 81041)



Threaded Plunger Syringes are for applications requiring extremely precise plunger movement or minute fluid manipulation. You can dispense from 0.33 to 37.79 μ L per plunger revolution depending on the syringe volume.

Product Specifications

Volume	100 μL
Syringe Type	Gastight
Syringe Series	1700
Termination	Luer Tip (LT)
Needle	Kel-F Hub
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Fluid Path	Borosilicate glass, PTFE
Autoclavable	Yes to 115 °C
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	115°C / 239°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.057 inches (1.46 mm)



EU: +40-356-635-055



Barrel Outer Diameter	0.305 inches (7.75 mm)	
Volume per rotation	1.32 μL	
Std Needle Dead Volume	N/A	
Sales Quantity	1 syringe per pack	
Specifications are subject to change without notice		Spec. Version B

https://www.hamiltoncompany.com/laboratory-products/syringes/81041



US: +1-800-648-5950 EU: +40-356-635-055