

10 mL Gastight Syringe Model 1010 TLL, PTFE Luer Lock, Needle Sold Separately

Specification Sheet (Part/REF # 81620)



10 mL Gastight Syringe Model 1010 TLL. Our syringes provide the accuracy and precision that enables many of the automated processes around the laboratory.

Product Specifications

Volume	10 mL
Syringe Type	Gastight
Syringe Series	1000
Termination	PTFE Luer Lock (TLL)
Needle	Metal (N) or Kel-F
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Plunger Style	X-Style
Fluid Path	Borosilicate glass, PTFE
Autoclavable	Yes
Gas Sterilizable	Yes
Pressure	200 psig (13.8 bar)
Maximum Temperature	115°C / 239°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.574 inches (14.6 mm)

Barrel Outer Diameter	0.695 inches (17.7 mm)
------------------------------	------------------------

Std Needle Dead Volume	N/A
-------------------------------	-----

Sales Quantity	1 syringe per pack
-----------------------	--------------------

Specifications are subject to change without notice

Spec. Version B

<https://www.hamiltoncompany.com/laboratory-products/syringes/81620>