

25 mL Gastight Syringe Model 1025 TLL, PTFE Luer Lock, Needle Sold Separately

Specification Sheet (Part/REF # 82520)



The 1000 series syringes are a mid-volume Gastight syringe. This series of syringes is ideal for dispensing volumes from 1 mL up to 100 mL. A variety of different terminations and needle options are available in this series.

Product Specifications

Volume	25 mL
Syringe Type	Gastight
Syringe Series	1000
Termination	PTFE Luer Lock (TLL)
Needle	Metal (N) or Kel-F
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Fluid Path	Borosilicate glass, PTFE, PCTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	100 psig (6.9 bar)
Maximum Temperature	80°C / 176°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.907 inches (23.0 mm)
Barrel Outer Diameter	1.07 inches (27.1 mm)



US: +1-800-648-5950 EU: +40-356-635-055



Std Needle Dead Volume	N/A	
Sales Quantity	1 syringe per pack	
Specifications are subject to change without notice		Spec. Version B

https://www.hamiltoncompany.com/laboratory-products/syringes/82520



Visit www.hamiltoncompany.com/support to find a representative in your area or call us:

US: +1-800-648-5950 EU: +40-356-635-055