## HAMILT®N

## 100 mL Gastight Syringe Model 1100 TLL, PTFE Luer Lock, Needle Sold Separately

Specification Sheet (Part/REF # 86020)



The 1000 series syringes are a mid-volume Gastight syringe. This series of syringes is ideal for dispensing volumes from 1 mL up to 100 mL. A variety of different terminations and needle options are available in this series.

## **Product Specifications**

Volume	100 mL
Syringe Type	Gastight
Syringe Series	1000
Termination	PTFE Luer Lock (TLL)
Needle	Metal (N) or Kel-F
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Fluid Path	Borosilicate glass, PTFE, PCTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	100 psig (6.9 bar)
Maximum Temperature	80°C / 176°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	1.28 inches (32.6 mm)
Barrel Outer Diameter	1.45 inches (36.9 mm)



Visit <u>www.hamiltoncompany.com/support</u> to find a representative in your area or call us: US: +1-800-648-5950 EU: +40-356-635-055

## HAMILTON

Std Needle Dead Volume

N/A

Sales Quantity

1 syringe per pack

Specifications are subject to change without notice

https://www.hamiltoncompany.com/laboratory-products/syringes/86020

Spec. Version B



Visit <u>www.hamiltoncompany.com/support</u> to find a representative in your area or call us: US: +1-800-648-5950 EU: +40-356-635-055