

2 L Super Syringe Model S2000 TLL, PTFE Luer Lock, Needle Sold Separately

Specification Sheet (Part/REF # 86314)



Super Syringes are extremely high volume Gastight syringes. The work best with volumes between 500 mL to 2 L.

Product Specifications

Volume	2 L
Syringe Type	Gastight
Syringe Series	Super Syringe
Termination	PTFE Luer Lock (TLL)
Needle	Metal (N) or Kel-F
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Fluid Path	Buna-N, Nickel plated brass, PTFE, Silicone, Acrylic
Autoclavable	No
Gas Sterilizable	Yes
Pressure	30 psig (2.1 bar)
Maximum Temperature	80°C / 176°F
Minimum Temperature	0°C / 32°F
Barrel Inner Diameter	3.44 inches (87.4 mm)
Barrel Outer Diameter	3.95 inches (100 mm)
Std Needle Dead Volume	N/A



Visit www.hamiltoncompany.com/support to find a representative in your area or call us:

US: +1-800-648-5950 EU: +40-356-635-055



Sales Quantity 1 syringe per pack

Specifications are subject to change without notice

Spec. Version B

https://www.hamiltoncompany.com/laboratory-products/syringes/86314



Visit www.hamiltoncompany.com/support to find a representative in your area or call us:

US: +1-800-648-5950 EU: +40-356-635-055