

5 μL Microliter Syringe Model 75 N, Cemented Needle, 26s gauge, 2 in, point style 2

Specification Sheet (Part/REF # 87900)



The 700 series syringe is the original hand-fitted Hamilton syringe. This series of syringes is ideal for dispensing volumes from $0.5~\mu L$ up to $500~\mu L$. A variety of different terminations and needle options are available in this series.

Product Specifications

Volume	5 μL
Syringe Type	Microliter
Syringe Series	700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	26s gauge
Point Style	2
Needle Length	2 inch (51 mm)
Fluid Path	SST, borosilicate glass
Autoclavable	No
Gas Sterilizable	Yes
Pressure	2000 psig (137.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.014 inches (0.343 mm)
Barrel Outer Diameter	0.260 inches (6.60 mm)



US: +1-800-648-5950 EU: +40-356-635-055



Needle Inner Diameter	0.005 inches (0.13 mm)	
Needle Outer Diameter	0.019 inches (0.483 mm)	
Std Needle Dead Volume	0.64 μL	
Sales Quantity	1 syringe per pack	
Specifications are subject to change without notice		Spec. Version B

https://www.hamiltoncompany.com/laboratory-products/syringes/87900



US: +1-800-648-5950 EU: +40-356-635-055