

## Electric Overhead Stirrer



### Features:

- ▶ The LCD screen displays the set speed and actual speed, which is intuitive and clear (T60 - T120 series);
- ▶ DC permanent magnet motor, low noise, maintenance-free, stable operation;
- ▶ Constant speed, torque can be adjusted automatically according to the change of sample viscosity;
- ▶ Adjustable stirring rod chuck, easy to load and unload;
- ▶ The overload will stop automatically to ensure safe operation;
- ▶ Automatically switch the circuit under abnormal conditions to ensure safe use.
- ▶ Stable start-up, effectively preventing sample overflow;
- ▶ Automatically memorize the final set working parameters, multi-segment programming control.

### LARGE LCD DISPLAY



### SAFETY PROTECTION



- OVERLOAD PROTECTION**
- OVER SPEED PROTECTION**
- SAFETY CIRCUIT**
- NON-SLIP MAT FOR STABILITY**



## Technical Specifications:

Model	LS-T50	LS-T100	LS-T60	LS-T120
Power Supply	AC100-240		AC100-240	
Hz	50-60		50-60	
Power(W)	72w	120w	72w	120w
Display	LCD display		LCD display	
Speed Range(rpm)	100-2000rpm		100-2000rpm	
Speed Control Accuracy	±10rpm		±10rpm	
Max Mixing (H <sub>2</sub> O) L	20L	40L	20L	40L
Recommend Mixing (H <sub>2</sub> O) L	5L	10L	5L	10L
Max Stirring Viscosity(mPa·s)	10.000	20.000	10.000	20.000
Lifting Stroke(mm)	300-600	300-600	300-600	300-600
Motor Type	DC permanent magnet motor		DC permanent magnet motor	
Timing	/		0-99h59min	
Net Weight(Kg)	8kg	9kg	8kg	9kg
Dimensions(mm)	325×215×600		325×215×600	

### LS-T50 , LS-T100



### LS-T60 , LS-T120

