

MS-PA LED Digital Magnetic Stirrer

Features

- Broad speed range from 100-1500rpm.
- Suitable for high speed mixing applications.
- Max. Stirring quantity is 3L [H₂O].
- LED digital speed control.
- Good chemical performance workplate.



MS-PB Magnetic Stirrer

Features

- Broad speed range from 100-1500rpm.
- Suitable for high speed mixing applications.
- Max. Stirring quantity is 3L [H₂O].
- Good chemical performance workplate.



Specifications

	MS-PA	MS-PB
Work plate dimension[WXD]	φ135(5 inch)mm	φ135(5 inch)mm
Work plate material	N ylon+GF	N ylon+GF
Motor type	DC motor	DC motor
Motor input power	5W	5W
Motor output power	3W	3W
Power	15W	10W
Voltage	100-120/200-240V,50/60Hz	100-120/200-240V,50/60Hz
Stirring positions	1	1
Max. stirring quantity[H ₂ O]	3L	3L
Max. magnetic bar[length]	50mm	50mm
Speed range	100-1500rpm	0-1500rpm
Speed display	LED	Scale
Protection class	IP42	IP42
Dimension[WxDxH]	150×260×80mm	150×260×80 mm
Weight	1.8kg	1.8kg
Permissible ambient temperature and humidity	5-40°C, 80%RH	5-40°C, 80%RH