

7" inch hotplate magnetic Stirrers are suitable for various heating and mixing applications with excellent chemical resistance, compact shape and efficient heat transfer. They are widely used in every field of science like biology, chemistry, physical science, pharmaceutical science etc.

MS7-H550-Pro LCD Hotplate Magnetic Stirrer

Features

- Microprocessor PID controls.
- LCD display with speed and temperature control knobs.
- Ceramic work plate with a high power of 1050W reaches a maximum temperature of 550°C.
- Max. Heating temperature of 550°C.
- Ceramic workplate of 184x184mm inches.
- Speed is adjustable from 100 to 1500rpm.
- Safety indication on LCD when the plate temperature exceeds above 50°C.
- PT1000 External temperature sensor for precise temperature control.
- RS232 interface enables data preservation and control through a PC.



MS7-H550-S LED Hotplate Magnetic Stirrer

Features

- LED display with speed and temperature control knobs.
- Adjustable speed range: 0-1500rpm.
- Ceramic workplate with a maximum temperature of 550°C.
- PT1000 External temperature sensor for precise temperature control at an accuracy of $\pm 0.2^{\circ}\text{C}$
- "Hot" warning safety indication on LED when the plate temperature exceeds above 50°C.



Specifications	MS7-H550-Pro	MS7-H550-S
Work plate Dimension [W x D]	184x184mm (7 inch)	184x184mm (7 inch)
Work plate material	Glass ceramic	Glass ceramic
Motor type	Brushless DC motor	Shaded pole motor
Motor rating input	18W	15W
Motor rating output	10W	1.5W
Power	1050W	1030W
Heating output	1000W	1000W
Voltage	100-120/200-240V 50/60Hz	100-120/200-240V 50/60Hz
Stirring positions	1	1
Max. stirring quantity, [H ₂ O]	20L	10L
Max. magnetic bar[length]	80mm	80mm
Speed range	100-1500rpm resolution ±1rpm	0-1500rpm
Speed display	LCD	Scale
Temperature display	LCD	LED
Heating temperature range	Room Temp.-550°C, increment 1°C	Room temp.-550°C, increment 5°C
Temperature control accuracy	±1°C(<100°C) ±1%(>100°C)	±10°C
Overheating protection	580°C	580°C
Temperature display accuracy	±0.1°C	±1°C
External temperature sensor	PT1000 (accuracy ±0.2)	PT1000 (accuracy ±0.2)
"Hot" warning	50°C	50°C
Data connector	RS232	-
Protection class	IP21	IP21
Dimension [WxDxH]	215x360x112mm	215x360x112mm
Weight	5.3kg	4.5kg
Permissible ambient temperature and humidity	5-40°C, 80%RH	5-40°C, 80%RH